



Product data sheet

HKG316T2230

Characteristics

Digital time switch, HKG316T, 230/400 V AC, double output, internal alkaline battery



Main

Range of product	HKG
Product or component type	Programmable digital time switch
Device short name	HKG316T
Battery type	Alkaline

Complementary

Number of outputs	2.0
[Ie] rated operational current	AC-15: 3 A AC 50 Hz 240 V AC-15: 1.9 A AC 50 Hz 400 V
Rated control voltage	230/400 V AC
Maximum number of switchings	1.0 x 16 on - 16 off per day 2.0 x 8 on - 8 off per day
Rated thermal current	10 A
Accuracy	+/- 2 s/day
Display type	Digital display

Environment

Standards	IEC 60947-5-1
-----------	---------------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.