



**Product data sheet**

**HLD1122B21M5**

**Characteristics**

**Monolithic pilot light, HLD11, 220 V AC/DC, half cover head, long terminal, resistance type, yellow**



**Main**

Range of product	HLD11
Device presentation	Monolithic product
Product or component type	Pilot light
Head type	Half-cover head
Load type	Resistive
Bezel material	Plastic
Mounting diameter	22 mm

**Complementary**

[Us] rated supply voltage	220 V AC/DC
Shape of signaling unit head	Round
Shape	Long
Cap/operator or lens colour	Yellow
Connections - terminals	Screw clamp terminals
Service life in hours	30000 h
E-commerce address	Hld11

**Environment**

Standards	IEC 60947-5-1
IP degree of protection	IP65

**Packing Units**

Unit Type of Package 1	PCE
Number of Units in Package 1	1

**Offer Sustainability**

Sustainable packaging	No
-----------------------	----

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.