



Product data sheet

HRT1863ZB

Characteristics

Cylindrical fuse, HRT18, 63 63A



Product Image Coming Soon

Main

| | |
|---------------------------|----------------|
| Range of product | HRT18 |
| Product or component type | Cartridge fuse |
| Fuse type | Cylindrical |
| Device application | Protection |
| Fuse curve | GG |

Complementary

| | |
|--------------------------------|----------------|
| [Ue] rated operational voltage | 380...500 V AC |
| [In] rated current | 63 A |

Environment

| | |
|---------------------------------------|------------|
| Standards | EN 60269 |
| Product certifications | CE |
| Ambient air temperature for operation | -5...40 °C |
| Operating altitude | = 2000 m |

Packing Units

| | |
|------------------------------|-----|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |

Offer Sustainability

| | |
|-----------------------|----|
| Sustainable packaging | No |
|-----------------------|----|

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.